

List of TakeCharge Qualifying HRV Models
Updated: May 2026

Brand Name	Model		
Airflow	AIR-265-R	Greentek	SOLACE 1.2E-EC
Airflow	AIR100HEXF	Greentek	SOLACE 1.2H
Airflow	AIR155R	Greentek	SOLACE 1.5H
Airflow	AIR205-R	Greentek	SOLACE 1.5H-EC
ALDES	H190TQG	Greentek	SOLACE 1.6E-EC
ALDES	H190TRG	Greentek	SOLACE 2.5H-EC
ALDES	H190TRGNOVO	Greentek	SOLACE 2.0H
ALDES	H280SRG	Greentek	PREMIER 3.0E-EC
ALDES	H80HR	Healthy Climate	HRV5270TPDECM
ALDES	H80HRNOVO	Healthy Climate	HRV3-195
Alnor	HRU-MinistAIR-NA-L-325	Healthy Climate	HRV5-150
Alnor	HRU-PremAIR-NA-450	Healthy Climate	HRV5-200-TPD
Alnor	HRU-SlimAIR-NA-250	Healthy Climate	HRV6-HEX095-TPD
Auroris	HSH-160ES	Lennox	HRV3300
Broan	B150H75NS	Lifebreath	267MAX
Broan	B180H75RT	Lifebreath	100ECM
Broan	B230H75RS	Lifebreath	155MAX
Broan	B230H75RT	Lifebreath	195DCS
Broan	V130H80RT	Lifebreath	195ECM
Broan	V150H75NS	Lifebreath	205MAX
Broan	V150H75NT	Lifebreath	300DCS
Broan	V160H75RS	Lifebreath	RNC155
Broan	V160H80RT	Lifebreath	RNC205
Broan	V180H75RT	Lifebreath	RNC5HEXTPF
Broan	V230H75RS	Lifebreath	RNC6 HEX TPD
Broan	V230H75RT	NEKTRA	NEKTRA 200
Broan	B180H75NT	Nu-Air	EL1300
Broan	B230H75NT	Nu-Air	ES150
Broan	B150H75NT	Nu-Air	NU145
Broan	B160H75RS	Reversomatic	RHRV-AB150PECM
Broan	B160H75RT	Reversomatic	RHRV-D100PECM
Broan	HRV200 ECM	Reversomatic	RHRV-120PES
Broan	HRV250 ECM	Reversomatic	RHRV-D100P ECM
Carrier	HRVXXLHB1230	Softaire	RHRV-130PES
Carrier	HRVXXSVB1160	Systemair	SOLACE 1.5H - EC
Carrier	HRV200ECM	vanEE	G2400H ECM
Carrier	HRV250ECM	vanEE	V160H75RT
Carrier	HRVXXSHB1160	Venmar	PRO 215 HRV
Clean Comfort	VH30120TRP	Venmar	X24HRV ECM N
Clean Comfort	VH30150TRP	Venmar	X30HRV ECM N
Clean Comfort	VH30140RNC	Venmar	A150H75NS
Direct Air	PHRVR120-HE	Venmar	A150H75NT
Direct Air	PHRVR150-HE	Venmar	A160H75RS
Direct Air	PHRVR200-HE	Venmar	A160H75RT
Fantech	HERO 120H	Venmar	A160H80RT
Fantech	HERO 120E-EC	Venmar	A180H75RT
Fantech	HERO 150H	Venmar	A230H75RS
Fantech	HERO 150H-EC	Venmar	A230H75RT
Fantech	HERO 160E-EC	Venmar	G3000H ECM
Fantech	HERO 250H-EC	Venmar	X24HRV ECM
Fantech	HERO 200H	Venmar	X30HRV ECM
Fantech	ATMO 300E-EC	Vents	BRIG HRV 200 R PR EC

These models meet the TakeCharge SRE and Fan Efficacy Requirements shown below:

Minimum SRE at	Minimum SRE at
32°F (0°C)	-13°F (-25°C)
70%	63%

Fan Efficacy of at least 1.2 cfm/W or 0.8 cfm/W if SRE is 75+